
Sorting description


Dinesen Pine



Dinesen

Dinesen Pine

Classic



- Subtle structure with a classic expression
- Harmonious and calm
- Fewer knots

Natural



- Vibrant structure with a natural expression
- Authentic and warm
- More knots

Elegant, beautiful and honest. Three words that characterize Dinesen Pine, which is a collection of unique plank flooring in pinewood.

Dinesen Pine is made of European raw wood sourced mainly from three select forest areas in Germany. Here, the trees slowly grow big and straight and are typically not felled until they are between 120 and 220 years old. The felling takes place in winter, just after the first frost.

We only use the lower 5-12 metres of the trunk, which typically has a diameter of 40 to 55 cm. German pine trees have fewer but slightly larger knots than Nordic ones.

The old trees are utilized respectfully. After being cut, dried and planed the planks are sorted into three qualities, of which only the two top ones are used for flooring.

Both these qualities have dense growth rings. The ratio of heartwood varies. The planks generally contain few knots. Knots in poor condition are replaced with fresh ones, and small knot holes are repaired.

General notes on quality

Our knowledge of wood has been passed down throughout the company's long history. We know everything there is to know about top-grade raw wood and the art of producing exclusive floors in uncompromising quality, and we continue to strive for perfection every single day. At Dinesen we appreciate direct contact. It is crucial for us to stay in close touch with every link of the chain – from the foresters fell the trees in the woods to the counselling of our clients. That is the only way to maintain our high consistent level of quality.

Dinesen Pine

Dinesen Pine is made of European raw wood sourced mainly from forests in southern Germany. The planks are produced of select raw wood cut from the lower 5–12 metres. The trees are felled when they are between 120 and 220 years old. Having survived everything, they have been subjected to, these are mature trees with a high degree of stability and durability. The long lifespan leads to top-quality raw wood. This quality applies to all variants and dimensions of our planks and is fully reflected in the finished floor.

The eye of the needle

Each tree is selected based on quality criteria such as straightness, growth rings, knots and overall harmony, and few trees pass the test. Only the best make it through the eye of the needle, and we take the utmost care in utilizing the selected trees.

Knots

Wood is a living material, and we strive to deliver harmonious floors, where the deep appreciation of nature is visible. Knots are the part of the branch that is embedded inside the trunk, and as such they are testimony to the history and vitality of the tree. Due to their high age and slow growth, the pine trees may contain fresh knots, dark knots and knot holes. Dinesen does not deliver knot-free flooring, because knots are a natural component of the tree. Instead, we take special care of the knots. If necessary, they are repaired or replaced in our quality control. New knots are painstakingly attached with a special knot glue. This safeguards both the quality of the plan and a respectful use of the tree that has been felled.

The number and sizes of knots that are allowed are the result of an individual assessment as part of our quality assurance process, based on the length and width of the plank and its overall visual appearance. Thus, we cannot define a precise specification. The number and sizes of knots depends in part on the width and length of the individual plank, including med the degree of pith repairs and so forth.

The photos on the following pages offer a representative but not exhaustive impression of the number of knots, grain structure and visual appearance overall.

Dinesen Pine

— Classic

Subtle structure with a classic expression.
Harmonious and calm. Fewer knots.



Images are only indicative.

Dinesen Pine

— Natural

Vibrant structure with a natural expression.
Authentic and warm. More knots.



Images are only indicative.

This sorting description and photo series offers a representative but not exhaustive impression of the number of knots, grain structure and visual appearance overall. The sorting description does not cover all variants and natural occurrences. Thus, 2-3% of the planks must be expected to display minor deviations.

A Dinesen floor is a natural product in the best sense of the word, and the sorting will thus always reflect the natural character of the wood.

The planks are CE-labelled and produced in accordance with Dinesen's factory standards with reference to EN 14342;2013.

Declaration of Performance: Pine DoP 2019-03 is available at dinesen.com.

Drying, sorting and production take place in Denmark, at our factory in the town of Jels. The planks are delivered with a moisture content of 8-10% and are suited for underfloor heating.

The planks are delivered unfinished and need to be sanded and finished as part of the installation. Dimensions and thicknesses are defined in the current price list, which is available at dinesen.com

We refer you to our general guidelines for additional information.

Full lengths

Planks are produced in lengths ranging from 1 m up to 10 m, as these are the lengths enabled by the raw wood.

Random lengths

Planks are produced in random lengths within a defined interval, for example 1-3 m or 2-5 m. The planks are produced continually, as the raw wood allows, and we aim for an average length in the middle of the interval with a few shorter and longer planks. The planks are profiled on all four sides.

We assume no liability for typos.

Dinesen
Klovtoftvej 2, Jels
6630 Rødding
Danmark

+45 7455 2140
info@dinesen.com
dinesen.com